




GENERAL FEATURES

- Angle measurement up to 360°
- 4-20 mA, 0-5V, 0-10V or CANopen signal output option
- Redundant output option
- Compensated axis sensitivity
- High Sensitivity : $\pm 0.1^\circ$
- Ability to specify 0° point
- Easy installation
- IP67 protection class
- Small and robust housing
- Compact structure



INC 210 series angle sensors are the sensors that show the angle of rotation of objects standing perpendicular to the earth. Angle measurement information between 0°-360° can be taken from these sensors. These sensors with 0-5VDC or 0-10VDC voltage output, 4-20mA current output or CANopen signal output option, can take measurement with $\pm 0.1^\circ$ accuracy.

These sensors, especially used in machine and crane industries, can operate in outdoor environments with their high IP protection classes. Optionally, sensors with redundant output can be produced.

TECHNICAL SPECIFICATIONS

Supply Voltage	4-20 mA & CANopen: 12...24 VDC 0-10 VDC & 0-5 VDC: 15...24 VDC	Protection Class	IP67
*Measurement Range	0° ... 360°	Operating Temperature	- 30°C ... +70°C
*Output Signals	Analog 4-20 mA, 0-5VDC, 0-10 VDC CANopen Opsiyonel Redundant Output	Relative Humidity	%10 ... %90
Resolution	For analog models: 12 bit For CANopen models: 0.05°	Weight	~250 gr
Accuracy	$\pm 0,1^\circ$	Body Material	Aluminium
		*Electrical Connection	Analog models: M12 5 pin (male) socket or cable output CANopen models: M12 5 pin (male) and M12 5 pin (female) socket

Note: The specifications specified by (*) vary depending on the model selected. The detailed code table for product selection is shown on page 4.

CANopen SPECIFICATIONS

Communication profile	CiA 301
Response Rate	10 Hz.
Device Type	CANopen, CiA DS410
Node ID	Between 1 and 127, it can be adjusted with LSS or SDO
Baud Rate	10 kBit/s, 20 kBit/s, 50 kBit/s, 100 kBit/s, 125 kBit/s, 250 kBit/s, 500 kBit/s, 800 kBit/s, 1 Mbit/s
PDO Data Rate	100 ms
Error Control	Heartbeat, Emergency Message
PDO	1 Tx PDO
PDO Modes	Event/Time triggered, Synch/Asynch
SDO	1 server
Position Information	Object Dictionary 6004
Termination Resistance	Optional, specify at the order stage.

ELECTRICAL CONNECTION

Analog

Signal	M12 Socket	Cable
V+	Pin 1	Red
Output1 (Analog current/voltage) (X axis)	Pin 2	Yellow
GND (0V)	Pin 3	Black
Output2 (Analog current/voltage) (Y axis)	Pin 4	Green
Reset	Pin 5	Pink

* Output 2 is only used on two-axis models. On single-axis models, Pin 4 (green cable) is empty.

* On single output models, 1 pcs M12 5 pin male socket is used as standard.

* Redundant models have two outputs. 1 pcs M12 5 pin male ve 1 pcs M12 5 pin female socket is used as standard.

* Different socket models can be requested optionally.

DETERMINING THE 0° POINT OF SENSOR

Pin 5 (pink cable) and pin 3 (black cable) are short-circuited for about 5 seconds and then disconnected. Thus, the sensor recognizes that the position is 0°. If the same operation is repeated a second time, the sensor is reset to the factory settings.

During the operations, the sensor position should be kept constant for approximately 4 seconds.


CANopen

Sinyal	M12 Soket	Kablo
CAN_SHIELD	Pin 1	Örgü
V+	Pin 2	Kırmızı
GND (0V)	Pin 3	Siyah
CAN_H	Pin 4	Sarı
CAN_L	Pin 5	Yeşil


* CANopen models have 2 outputs. 1 pcs M12 5 pin male and 1 pcs M12 5 pin female sockets are used as standard.

* Different socket models can be requested optionally.

M12 5 Pin Female Socket




M12 5 Pin Male Socket



MEASUREMENT AXIS AND SIGNAL OUTPUT DIAGRAM






Analog Signal Output






MECHANICAL DIMENSIONS (in mm)

Analog



CANopen




SAMPLE APPLICATION AREAS

- Agricultural and forestry machinery
- Construction machinery and special-purpose vehicles
- Solar thermal energy and photovoltaics
- Automated guided systems
- Crane and lifting technology
- Wind power plant



ORDER CODE



- (1) The supply voltage is 12...24VDC for CANopen and 4-20 mA output models, and 15...24VDC for 0-10 VDC and 0-5 VDC output models.
- (2) Optionally, different measurement values between $\pm 90^\circ$ can be requested. You should specify your non-standard measurement value at the order stage.
- (3) The product can be requested with cable or socket.
As standard;
For single output models, 1 pcs M12 5 pin male socket (S13M) is used.
For redundant and CANopen output models, 1 pcs M12 5 pin female + 1 pcs M12 5 pin male socket (S13FM) is used.
However, different socket combinations may be requested as in the examples below.
Please contact us for any other socket model other than M12.

Sample Code 1: INC210- 01-360-PP-A-CW-S13F

INC 210 series, single axis, measurement between 0...360°, 12-24VDC supply, clockwise, 1 pcs M12 5 pin female socket, single output

Sample Code 2: INC210- 01-180-PP-C-CCW-S13FM-DUAL

INC 210 series, single axis, measurement between 0...180°, 12-24VDC supply, CANopen output, counter-clockwise, 1 pcs M12 5 pin female + 1 pcs M12 5 pin male socket, redundant output

Sample Code 3: INC210- 01-180-PP-C-CCW-S13M

INC 210 series, single axis, measurement between 0...180°, 12-24VDC supply, CANopen output, counter-clockwise, 2 pcs M12 5 pin male socket

OPTIONAL PRODUCTS

Product	Code	Description
	CB5 5M / S13F	5 meters 5x0,14 mm ² extension cable + M12/5 pin female connector (IP67)

Atek Elektronik Sensör Teknolojileri Sanayi ve Ticaret A.Ş.

 Gebze OSB, 800. Sokak, No:814 Gebze/KOCAELİ/TURKEY

 Tel: +90 262 673 76 00

 Fax: +90 262 673 76 08

 www.ateksensor.com

 info@ateksensor.com